

ASTM F891 Solvent Weld PVC Foam Core DWV Pipe Certification

ASTM F891 Solvent Weld PVC Foam Core Drain, Waste, and Vent Pipe (sizes 1-1/2" through 6", IPS Schedule 40), provided by NAPCO, is manufactured in accordance with **ASTM F891**. The PVC material conforms to a minimum cell classification of 11432 as defined by **ASTM D4396**. ASTM F891 products are produced in both plain end and solvent weld bell end configurations with standard laying lengths of 10, or 20 feet. Pipe supplied for DWV applications is white in color.

ASTM F891 products manufactured are listed by NSF International to **NSF 14**.

Certifications are based on the applicable edition of the referenced standard in effect on the date of manufacture. If we may be of further assistance, please contact Technical Services at technical@westlakepipe.com.

Sincerely,



Joshua E. Clapper
Director, Product Marketing, Marketing and Development

Reference Standards:

- **ASTM D4396** *Standard Specification for Rigid Poly(Vinyl Chloride) (PVC) and Chlorinated Poly(Vinyl Chloride) (CPVC) Compounds for Plastic Pipe and Fittings Used in Nonpressure Applications*
- **ASTM F891** *Standard Specification for Coextruded Poly(Vinyl Chloride) (PVC) Plastic Pipe with a Cellular Core*
- **NSF 14** *Plastics Piping System Components and Related Materials*